

Section 1. Identification

Product name Castrol GTX ULTRACLEAN 5W-20
SDS # 469249
Code 469249-US12

Relevant identified uses of the substance or mixture and uses advised against

Product use Engine Oils.
 For specific application advice see appropriate Technical Data Sheet or consult our company representative.

Supplier BP Lubricants USA Inc.
 1500 Valley Road
 Wayne, NJ 07470
 Telephone: 1-888-CASTROL

EMERGENCY HEALTH INFORMATION: 1 (800) 447-8735
 Outside the US: +1 703-527-3887 (CHEMTREC)

EMERGENCY SPILL INFORMATION: 1 (800) 424-9300 CHEMTREC (USA)

Section 2. Hazards identification

OSHA/HCS status This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture Not classified.

GHS label elements

Signal word No signal word.
Hazard statements No known significant effects or critical hazards.

Precautionary statements

Prevention Not applicable.
Response Not applicable.
Storage Not applicable.
Disposal Not applicable.

Hazards not otherwise classified Defatting to the skin.
 USED ENGINE OILS
 Used engine oil may contain hazardous components which have the potential to cause skin cancer.
 See Toxicological Information, section 11 of this Safety Data Sheet.

Section 3. Composition/information on ingredients

Substance/mixture Mixture
 Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

| Ingredient name | % | CAS number |
|--|-----|------------|
| Distillates (petroleum), hydrotreated heavy paraffinic | ≤10 | 64742-54-7 |
| Distillates (petroleum), hydrotreated heavy paraffinic | ≤3 | 64742-54-7 |

Product name Castrol GTX ULTRACLEAN 5W-20 **Product code** 469249-US12 **Page:** 1/9
Version 19.06 **Date of issue** 01/08/2024. **Format** CCSA **Language** ENGLISH

Section 3. Composition/information on ingredients

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

| | |
|-----------------------------------|---|
| Eye contact | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention. |
| Skin contact | Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur. |
| Inhalation | If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur. |
| Ingestion | Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur. |
| Protection of first-aiders | No action shall be taken involving any personal risk or without suitable training. |

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

| | |
|----------------------------|---|
| Notes to physician | Treatment should in general be symptomatic and directed to relieving any effects. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Specific treatments | No specific treatment. |

Section 5. Fire-fighting measures

Extinguishing media

| | |
|---------------------------------------|--|
| Suitable extinguishing media | In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray. |
| Unsuitable extinguishing media | Do not use water jet. |

Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products

Combustion products may include the following:
carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)
nitrogen oxides (NO, NO₂ etc.)

Special protective actions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

| | |
|------------------------------------|--|
| For non-emergency personnel | No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling. |
|------------------------------------|--|

Section 6. Accidental release measures

For emergency responders If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures Put on appropriate personal protective equipment (see Section 8).

Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Not suitable Prolonged exposure to elevated temperature

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Distillates (petroleum), hydrotreated heavy paraffinic

OSHA PEL (United States). [Oil mist, mineral]

TWA: 5 mg/m³ 8 hours. Issued/Revised: 6/1993

ACGIH TLV (United States). [Mineral Oil, pure, highly and severely refined]

TWA: 5 mg/m³ 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction

Distillates (petroleum), hydrotreated heavy paraffinic

OSHA PEL (United States). [Oil mist, mineral]

TWA: 5 mg/m³ 8 hours. Issued/Revised: 6/1993

ACGIH TLV (United States). [Mineral Oil, pure, highly and severely refined]

TWA: 5 mg/m³ 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction

Biological exposure indices

No exposure indices known.

Section 8. Exposure controls/personal protection

Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety glasses with side shields.

Skin protection

Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Body protection

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

| | |
|----------------|----------------|
| Physical state | Liquid. |
| Color | Brown. |
| Odor | Not available. |
| Odor threshold | Not available. |

Section 9. Physical and chemical properties

| | |
|--|---|
| pH | Not applicable. |
| Melting point/freezing point | Not available. |
| Boiling point, initial boiling point, and boiling range | Not available. |
| Flash point | Open cup: >200°C (>392°F) [Cleveland ASTM D 92] |
| Pour point | -41 °C |
| Evaporation rate | Not available. |
| Flammability | Not applicable. Based on - Physical state |
| Lower and upper explosion limit/flammability limit | Not available. |
| Vapor pressure | |

| Ingredient name | Vapor Pressure at 20 °C | | | Vapor pressure at 50 °C | | |
|--|-------------------------|--------|-------------|-------------------------|-----|--------|
| | mm Hg | kPa | Method | mm Hg | kPa | Method |
| Distillates (petroleum), hydrotreated heavy paraffinic | <0.08 | <0.011 | ASTM D 5191 | | | |
| Distillates (petroleum), hydrotreated heavy paraffinic | <0.08 | <0.011 | ASTM D 5191 | | | |

| | |
|-------------------------------|---|
| Relative vapor density | Not available. |
| Density | <1000 kg/m ³ (<1 g/cm ³) at 15°C |
| Solubility(ies) | |

| Media | Result |
|-------|-------------|
| water | Not soluble |

| | |
|---|---|
| Partition coefficient: n-octanol/water | Not applicable. |
| Auto-ignition temperature | Not available. |
| Decomposition temperature | Not available. |
| Viscosity | Kinematic: 50.66 mm ² /s (50.66 cSt) at 40°C Kinematic: 8.2 to 9.2 mm ² /s (8.2 to 9.2 cSt) at 100°C |
| Particle characteristics | |
| Median particle size | Not applicable. |

Section 10. Stability and reactivity

| | |
|---|---|
| Reactivity | No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information. |
| Chemical stability | The product is stable. |
| Possibility of hazardous reactions | Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not occur. |
| Conditions to avoid | Avoid all possible sources of ignition (spark or flame). |
| Incompatible materials | Reactive or incompatible with the following materials: oxidizing materials. |
| Hazardous decomposition products | Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

Section 11. Toxicological information

Information on toxicological effects

Aspiration hazard

| Name | Result |
|--|--------------------------------|
| Distillates (petroleum), hydrotreated heavy paraffinic | ASPIRATION HAZARD - Category 1 |

Information on the likely routes of exposure

Routes of entry anticipated: Dermal, Inhalation, Eyes.

Potential acute health effects

| | |
|---------------------|--|
| Eye contact | No known significant effects or critical hazards. |
| Skin contact | No known significant effects or critical hazards. |
| Inhalation | Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure. |
| Ingestion | No known significant effects or critical hazards. |

Symptoms related to the physical, chemical and toxicological characteristics

| | |
|---------------------|--|
| Eye contact | No specific data. |
| Skin contact | Adverse symptoms may include the following: irritation dryness cracking |
| Inhalation | No specific data. |
| Ingestion | No specific data. |

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

| | |
|------------------------------------|----------------|
| Potential immediate effects | Not available. |
| Potential delayed effects | Not available. |

Long term exposure

| | |
|------------------------------------|----------------|
| Potential immediate effects | Not available. |
| Potential delayed effects | Not available. |

Potential chronic health effects

| | |
|------------------------------|---|
| General | USED ENGINE OILS Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained. |
| Carcinogenicity | No known significant effects or critical hazards. |
| Mutagenicity | No known significant effects or critical hazards. |
| Teratogenicity | No known significant effects or critical hazards. |
| Developmental effects | No known significant effects or critical hazards. |
| Fertility effects | No known significant effects or critical hazards. |

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

No testing has been performed by the manufacturer.

Persistence and degradability

Not expected to be rapidly degradable.

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Mobility in soil

Soil/water partition coefficient (K_{oc}) Not available.

Mobility Spillages may penetrate the soil causing ground water contamination.

Other adverse effects No known significant effects or critical hazards.

Other ecological information Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13. Disposal considerations

Disposal methods The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | DOT Classification | TDG Classification | IMDG | IATA |
|-----------------------------------|---------------------------|---------------------------|----------------|----------------|
| UN number | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| UN proper shipping name | - | - | - | - |
| Transport hazard class(es) | - | - | - | - |
| Packing group | - | - | - | - |
| Environmental hazards | No. | No. | No. | No. |
| Additional information | - | - | - | - |

Special precautions for user Not available.

Transport in bulk according to IMO instruments Not available.

Section 15. Regulatory information

U.S. Federal regulations

United States inventory (TSCA 8b) All components are active or exempted.

Other regulations

Australia inventory (AIIIC) All components are listed or exempted.

Canada inventory All components are listed or exempted.

China inventory (IECSC) All components are listed or exempted.

Japan inventory (CSCL) At least one component is not listed.

Korea inventory (KECI) All components are listed or exempted.

Philippines inventory (PICCS) All components are listed or exempted.

Taiwan Chemical Substances Inventory (TCSI) All components are listed or exempted.

REACH Status For the REACH status of this product please consult your company contact, as identified in Section 1.

Section 16. Other information

History

Date of issue/Date of revision 01/08/2024.

Date of previous issue 01/08/2024.

Prepared by Product Stewardship Group

Key to abbreviations

ACGIH = American Conference of Industrial Hygienists
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS Number = Chemical Abstracts Service Registry Number
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OEL = Occupational Exposure Limit
SDS = Safety Data Sheet
STEL = Short term exposure limit
TWA = Time weighted average
UN = United Nations
UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods.
Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

▣ Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material.

Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be

Section 16. Other information

taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.